

## PROSPETTO DIFFERENZE VERSIONI YAESU VX-8

		VX-8E	VX-8DE	VX-8GE
APRS	Smart Beaconing	No	Yes	Yes
	Number of Station List Memories	40	50	50
	Number of Message List Storage	20	30	30
	Digi-Path Route display	No	Yes	Yes
	Digi-Path settings	1	8 Routes (3 fix, 5 selectable)	8 Routes (3 fix, 5 selectable)
	GPS Compass	North up	North or heading up	North or heading up
	Preset Symbol Icon	1 (VS)	4 (Person, Bicycle, Car, User(YY))	4 (Person, Bicycle, Car, User(YY))
	Autom. digit increment (when entering letters)	No	Yes	Yes
	LED flashing (when receiving message)	Not selectable	Selectable	Selectable
Features	AM/FM broadcast band RX	Yes	Yes	No
	Wide FM broadcast RX	Yes	Yes	No
	Frequency range RX	0.5 — 999.99 MHz	0.5 — 999.99 MHz	108.0 — 999.99 MHz
	Frequency range TX	50/144/430 MHz	50/144/430 MHz	144/430 MHz
	GPS Antenna	Optional	Optional	Internal
	Vibrator alert	No	No	Yes
	Waterproof	IPX7	IPX7	IPX5
	Bluetooth Option	Yes	Yes	No
	Barometric Option	Yes	Yes	No
	VOX	Yes	Yes	No
	Audio Wave monitor	Yes	Yes	No
	AF Dual	Yes	Yes	No
	Channel Counter	Yes	Yes	No
Data terminal	No	No	Yes RS-232 level. Possible to output the GPS position data and the received station location data. Possible to connect an external GPS antenna.	